

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of inducing a change in the baroreflex system of a patient, the method comprising the steps of:
providing an activation device; and;
positioning the activation device proximate a baroreceptor in a vascular wall so as to preferentially induce a physiologic change in the baroreceptor; and
automatically controlling an output of the activation device to induce the change in the baroreflex system, the activation device having an output which changes the output including a first level delivered for a first period of time to attain the physiologic change and a second level delivered for a second period of time to retain the physiologic change, wherein the first level attains the physiologic change more quickly than the second level and the second level is different than the first level over time so as to promote long term efficacy in inducing the change in the baroreflex system.

Claims 2-3 (Canceled).

4. (Currently Amended) A method as in claim 1, ~~[[3]]~~ wherein the second level is delivered independently of feedback from a sensor selected to retain the physiologic change.

5. (Original) A method as in claim 1, wherein the activation device mechanically, electrically, thermally, chemically or biologically induces the change in the baroreflex system.

6. (Previously Presented) A method as in claim 5, wherein the output of the activation device comprises an electrical signal, and wherein the electrical signal induces the change in the baroreflex system.

7. (Currently Amended) A method as in claim 6, wherein the electrical output signal has an amplitude, and wherein the amplitude of the first ~~output~~ level is different than the amplitude of the second ~~output~~ level.

8. (Currently Amended) A method as in claim 6, wherein the electrical output signal comprises a series of pulses having a pulse frequency, and wherein the pulse frequency of the first ~~output~~ level is different than the pulse frequency of the second ~~output~~ level.

9. (Currently Amended) A method as in claim 6, wherein the electrical output signal has a pulse width, and wherein the pulse width of the first ~~output~~ level is different than the pulse width of the second ~~output~~ level.

10. (Currently Amended) A method of claim 6, wherein the electrical output signal comprises a series of pulses delivered in bursts having a burst frequency, and wherein the burst frequency of the first ~~output~~ level is greater than the burst frequency of the second ~~output~~ level.

11. (Withdrawn) A method of inducing a baroreceptor to signal to affect a change in the baroreflex system in a patient, the method comprising the steps of:
providing a baroreceptor activation device having a first electrode and a second electrode;
positioning the first electrode at a first anatomical location proximate a baroreceptor;
positioning the second electrode at a second anatomical location proximate a baroreceptor, wherein the first location is different than the second location;
alternatively activating, deactivating or otherwise modulating the electrodes of the baroreceptor activation device.

12. (Withdrawn) A method as in claim 11, wherein the first anatomical location comprises a right carotid sinus, and wherein the second anatomical location comprises a left carotid sinus.

13. (Withdrawn) A method as in claim 11, wherein the first anatomical location is disposed immediately adjacent the second anatomical location.

14. (Withdrawn) A method of inducing a baroreceptor signal to affect a change in the baroreflex system in a patient, the method comprising the steps of:
providing a baroreceptor activation device;
positioning the baroreceptor activation device proximate a baroreceptor;
generating a control signal to activate, deactivate or otherwise modulate the baroreceptor activation device to induce a baroreceptor signal; and
changing the control signal to promote long term efficacy of inducing baroreceptor signals.

15. (Withdrawn) A method as in claim 14, wherein the baroreceptor activation device mechanically, electrically, thermally, chemically, or biologically induces the baroreceptor signal.

16. (Withdrawn) A method as in claim 15, wherein the baroreceptor activation device is activated, deactivated or otherwise modulated for a period of time having a start time and a duration, and wherein the start time and/or duration are changed to promote long term efficacy.

17. (Withdrawn) A method as in claim 16, wherein the start time is triggered by an event, and wherein the event is changed to promote long term efficacy.

18. (Withdrawn) A method as in claim 16, wherein the start time is triggered by an event with a delay between the event and the start time, and wherein the delay is changed to promote long term efficacy.

19. (Withdrawn) A method of inducing a baroreceptor signal to affect a change in the baroreflex system in a patient, the method comprising the steps of:
providing a baroreceptor activation device;

positioning the baroreceptor activation device proximate a baroreceptor;
generating an electrical signal from the baroreceptor activation device to
electrically induce a baroreceptor signal; and
changing the electrical signal to promote long term efficacy of inducing
baroreceptor signals.

20. (Withdrawn) A method as in claim 19, wherein the electrical signal has a frequency, and wherein the step of changing the electrical signal comprises changing the frequency.

21. (Withdrawn) A method of claim 19, wherein the electrical signal has a voltage, and wherein the step of changing the electrical signal comprises changing the voltage.

22. (Withdrawn) A method of claim 19, wherein the electrical signal as a polarity, and wherein the step of changing the electrical signal comprises changing the polarity.

23. (Withdrawn) A method as in claim 19, wherein the electrical signal has a waveform, and wherein the step of changing the electrical signal comprises changing the waveform.

24. (Withdrawn) A method as in claim 19, wherein the electrical signal as a phase, and wherein the step of changing the electrical signal comprises changing the phase.

25. (Withdrawn) A system for inducing a baroreceptor signal to affect a change in the baroreflex system in a patient, the system comprising:

a baroreceptor activation device positioned proximate a baroreceptor such that activation of the baroreceptor activation device includes a baroreceptor signal; and

a control system connected to the baroreceptor activation device, the control system including a processor and a memory, wherein the memory includes software defining a stimulus regimen, the control system generating a control signal as a function of the stimulus

regimen, the stimulus regimen causing a change in the control signal to promote long term efficacy of inducing baroreceptor signals.

26. (Previously Presented) A method as in claim 1, wherein the change in the baroreflex system comprises inducing a baroreceptor signal.

27. (Currently Amended) A method as in claim 6, wherein the electrical output signal comprises a series of pulses, each pulse having an amplitude, and wherein the amplitude of each pulse of the first ~~output~~ level is different than the amplitude of each pulse of the second ~~output~~ level.

28. (Currently Amended) A method as in claim 6, wherein the electrical output signal comprises a series of pulses, each pulse having a pulse width, and wherein the pulse width of each pulse of the first ~~output~~ level is different than the pulse width of each pulse of the second ~~output~~ level.